PAR16 DBT

Reflector Lamps

LR211053/dm/db-HRv00-2B+GU10+865+V0240

MEGAMAN®

GENERAL DESCRIPTION

Model Number	LR211053/dm/db-HRv00-2B	
Product Code	LR211053/dm/db-HRv00-2B+GU10+865+V0240	
Model Identifier	140520/MM10350	
Cap Base	GU10	
Dimmable	Only with specific dimmers	
Working Temperature	-30°C to +45°C	

TECHNICAL PARAMETERS

LIFE PERFORMANCE		
Indicative Lifetime L70B50 (hrs)	25000	at 25°C
Number of Switching Cycles	> 100000	

ELECTRICAL DATA

On-mode Power (W)	5.3	
Input Voltage	220-240 VAC	
Frequency	50/60 Hz	
Displacement Factor (cos φ1)	0.50	
Equivalent Power (W)	50	
Standby Power (W)	0.0	
Networked Standby Power (W)	N/A	
Survival Factor	0.90	
Lumen Maintenance Factor	0.93	

PHOTOMETRIC INFORMATION

Useful Luminous Flux (Im)	550
Useful Luminous Flux in 90° Cone (Im)	500
Useful Luminous Flux in 120° Cone (Im)	N/A
Correlated Colour Temperature (K)	6500
Colour Consistency	6
Colour Rendering Index	80
R9 Colour Rendering Index Value	0
Beam Angle (°)	24/35
Peak Luminous Intensity (cd)	3000/1800
Stroboscopic Effect Metric (SVM)	0.4
Flicker Metric (P _{st} ^{LM})	1.0
Chromaticity Coordinates (x and y)	0.329
	0.342

ENERGY EFFICIENCY

Weighted Energy Consumption (kWh/1000hrs)	6	
Energy Class	E	

CERTIFICATES & STANDARDS

Weight (g)

Standards Compliance	IEC/EN 62560, IEC/EN 62493, IEC/EN 62471, ErP 2019/2020, IEC 62612, IEC CISPR15, EN 55015, IEC/EN 61547, IEC/EN 61000-3-2, IEC/EN 61000-3-3
Approvals	CE, RoHS
DIMENSIONS & WEIGHT	
Height (mm)	56
Width (mm)	50
Depth (mm)	50

42

PAR16 DBT

Reflector Lamps LR211053/dm/db-HRv00-2B+GU10+865+V0240

50W/5.3W GU10 500Im 6500K Ra80 DBT U-Dim

MEGAMAN®

SPECIFIC PRECAUTIONS - GENERAL GUIDELINES



Dimming not allowed



Lamp suitable for dimming only with specific dimmers (A list of compatible dimmers shall be provided on the website www.megaman.cc)

Lamp not suitable for use if broken (its outer case)

Lamp not suitable for use under dust and moisture

Indoor use only

Turn off the lamp and let it cool down before any replacement

Do not run LED and incandescent lights on a trailer

For lamps with a weight significantly higher than that of the lamps for which they are a replacement, attention should be drawn to the fact that the increased weight may reduce the mechanical stability of certain luminaires and lamp holders and may impair contact making and lamp retention.

TESTING CONDITIONS

Refer to Annex A of IEC 62612 method of measuring lamp characteristics Light output and life hour are measured at 25° C, 230V

PAR16 DBT

Reflector Lamps

LR211053/dm/db-HRv00-2B+GU10+865+V0240

CALCULATIONS - GENERAL RULES

Refer to Annex II of Energy Labelling (EU) 2019/2015

Energy efficiency classes and calculation method

The energy efficiency class of light sources shall be determined as set out in Table 1, on the basis of the total mains efficacy η_{TM} , which is calculated by dividing the declared useful luminous flux Φ_{use} (expressed in *Im*) by the declared on-mode power consumption P_{on} (expressed in *W*) and multiplying by the applicable factor FTM of Table 2, as follows:

ηTM = (Φuse/Pon) × FTM (Im/W)

Table 1		
Energy efficiency classes of light sources		
Energy efficiency class Total mains efficacy ηTM (Im/W)		
A	210 ≤ ηTM	
В	185 ≤ ηTM < 210	
С	160 ≤ ηTM < 185	
D	135 ≤ ηTM < 160	
E	110 ≤ ηTM < 135	
F	85 ≤ ηTM < 110	
G	ηTM < 85	

Table 2		
Factors FTM by light source type		
Light source type	Factor FTM	
Non-directional (NDLS) operating on mains (MLS)	1,000	
Non-directional (NDLS) not operating on mains (NMLS)	0,926	
Directional (DLS) operating on mains (MLS)	1,176	
Directional (DLS) not operating on mains (NMLS)	1,089	

ADDITIONAL PART

A list of compatible dimmers shall be provided on the website www.megaman.cc

MEGAMAN GmbH Halskestraße 22-26, AircomParc A1 40880 Ratingen Germany



 $\ensuremath{\mathbb{C}}$ Copyright 2021. All rights reserved by $\ensuremath{\mathsf{MEGAMAN}}^{\ensuremath{\mathbb{B}}}$

12/7/2021



50W/5.3W GU10 500Im 6500K Ra80 DBT U-Dim