

PAR16 Glass

Reflector Lamps

LR6304.7dLN-WFL+GU10+865+V0240

MEGAMAN®

50W/4.7W GU10 345lm 6500K Ra80 Dimmable

GENERAL DESCRIPTION

Model Number	LR6304.7dLN-WFL
Product Code	LR6304.7dLN-WFL+GU10+865+V0240
Model Identifier	708113/MM08113
Cap Base	GU10
Dimmable	Only with specific dimmers
Working Temperature	-30°C to +45°C

TECHNICAL PARAMETERS

LIFE PERFORMANCE

Indicative Lifetime L70B50 (hrs)	15000	at 25°C
Number of Switching Cycles	> 100000	

ELECTRICAL DATA

On-mode Power (W)	4.7
Input Voltage	220-240 VAC
Frequency	50 Hz
Displacement Factor (cos φ1)	0.40
Equivalent Power (W)	50
Standby Power (W)	0.0
Networked Standby Power (W)	N/A
Survival Factor	0.90
Lumen Maintenance Factor	0.93

PHOTOMETRIC INFORMATION

Useful Luminous Flux (lm)	390
Useful Luminous Flux in 90° Cone (lm)	345
Useful Luminous Flux in 120° Cone (lm)	N/A
Correlated Colour Temperature (K)	6500
Colour Consistency	6
Colour Rendering Index	80
R9 Colour Rendering Index Value	0
Beam Angle (°)	36
Peak Luminous Intensity (cd)	650
Stroboscopic Effect Metric (SVM)	0.4
Flicker Metric (P _{st} ^{LM})	1.0
Chromaticity Coordinates (x and y)	0.329 0.342

ENERGY EFFICIENCY

Weighted Energy Consumption (kWh/1000hrs)	5
Energy Class	F

CERTIFICATES & STANDARDS

Standards Compliance	IEC/EN 62560, IEC/EN 62493, IEC/EN 62471, ErP 2019/2020, IEC 62612, IEC CISPR15, EN 55015, IEC/EN 61547, IEC/EN 61000-3-2, IEC/EN 61000-3-3
Approvals	CE, RoHS

DIMENSIONS & WEIGHT

Height (mm)	55
Width (mm)	50
Depth (mm)	50
Weight (g)	43

PAR16 Glass

Reflector Lamps

LR6304.7dLN-WFL+GU10+865+V0240



50W/4.7W GU10 345lm 6500K Ra80 Dimmable

SPECIFIC PRECAUTIONS - GENERAL GUIDELINES



Dimming not allowed



Lamp suitable for dimming only with specific dimmers
(A list of compatible dimmers shall be provided on the website
www.megaman.cc)



Lamp not suitable for use if broken
(its outer case)



Lamp not suitable for use under dust and moisture

Indoor use only

Turn off the lamp and let it cool down before any replacement

Do not run LED and incandescent lights on a trailer

For lamps with a weight significantly higher than that of the lamps for which they are a replacement, attention should be drawn to the fact that the increased weight may reduce the mechanical stability of certain luminaires and lamp holders and may impair contact making and lamp retention.

TESTING CONDITIONS

Refer to Annex A of IEC 62612 method of measuring lamp characteristics

Light output and life hour are measured at 25°C, 230V

PAR16 Glass

Reflector Lamps

LR6304.7dLN-WFL+GU10+865+V0240



50W/4.7W GU10 345lm 6500K Ra80 Dimmable

CALCULATIONS - GENERAL RULES

Refer to Annex II of Energy Labelling (EU) 2019/2015

Energy efficiency classes and calculation method

The energy efficiency class of light sources shall be determined as set out in Table 1, on the basis of the total mains efficacy η_{TM} , which is calculated by dividing the declared useful luminous flux Φ_{use} (expressed in lm) by the declared on-mode power consumption P_{on} (expressed in W) and multiplying by the applicable factor FTM of Table 2, as follows:

$$\eta_{TM} = (\Phi_{use}/P_{on}) \times FTM \text{ (lm/W)}$$

Table 1

Energy efficiency classes of light sources

Energy efficiency class	Total mains efficacy η_{TM} (lm/W)
A	$210 \leq \eta_{TM}$
B	$185 \leq \eta_{TM} < 210$
C	$160 \leq \eta_{TM} < 185$
D	$135 \leq \eta_{TM} < 160$
E	$110 \leq \eta_{TM} < 135$
F	$85 \leq \eta_{TM} < 110$
G	$\eta_{TM} < 85$

Table 2

Factors FTM by light source type

Light source type	Factor FTM
Non-directional (NDLS) operating on mains (MLS)	1,000
Non-directional (NDLS) not operating on mains (NMLS)	0,926
Directional (DLS) operating on mains (MLS)	1,176
Directional (DLS) not operating on mains (NMLS)	1,089

ADDITIONAL PART

A list of compatible dimmers shall be provided on the website www.megaman.cc

MEGAMAN GmbH
Halskestraße 22-26, AircomParc A1
40880 Ratingen
Germany



© Copyright 2021. All rights reserved by MEGAMAN®

11/26/2021