

MR16

Dim-to-Warm

ER200065/dw/ru-HRv00-WF+GU5.3+930918+C0350



39W/6.5W GU5.3 400lm 1800-3000K Ra97 Dim-to-Warm

GENERAL DESCRIPTION

Model Number	ER200065/dw/ru-HRv00-WF
Product Code	ER200065/dw/ru-HRv00-WF+GU5.3+930918+C0350
Model Identifier	709918/MM09918
Cap Base	GU5.3
Dimmable	Only with specific dimmers
Working Temperature	-30°C to +45°C

TECHNICAL PARAMETERS

LIFE PERFORMANCE

Indicative Lifetime L70B50 (hrs)	40000	at 25°C
Number of Switching Cycles	> 100000	

ELECTRICAL DATA

On-mode Power (W)	6.5
Input Voltage	16-20 VDC
Frequency	N/A
Displacement Factor (cos φ1)	N/A
Equivalent Power (W)	39
Standby Power (W)	0.0
Networked Standby Power (W)	N/A
Survival Factor	0.90
Lumen Maintenance Factor	0.96

PHOTOMETRIC INFORMATION

Useful Luminous Flux (lm)	430
Useful Luminous Flux in 90° Cone (lm)	400
Useful Luminous Flux in 120° Cone (lm)	N/A
Correlated Colour Temperature (K)	1800-3000
Colour Consistency	6
Colour Rendering Index	97
R9 Colour Rendering Index Value	75
Beam Angle (°)	36
Peak Luminous Intensity (cd)	1200
Stroboscopic Effect Metric (SVM)	N/A
Flicker Metric (P _{st} ^{LM})	N/A
Chromaticity Coordinates (x and y)	0.458 0.410

ENERGY EFFICIENCY

Weighted Energy Consumption (kWh/1000hrs)	7
Energy Class	G

CERTIFICATES & STANDARDS

Standards Compliance	IEC/EN 62838, IEC/EN 62493, IEC/EN 62471, ErP 2019/2020, IEC 62717, IEC CISPR15, EN 55015, IEC/EN 61547, IEC/EN 61000-3-2, IEC/EN 61000-3-3
Approvals	CE, RoHS

DIMENSIONS & WEIGHT

Height (mm)	46
Width (mm)	50
Depth (mm)	50
Weight (g)	45

MR16

Dim-to-Warm

ER200065/dw/ru-HRv00-WF+GU5.3+930918+C0350



39W/6.5W GU5.3 400lm 1800-3000K Ra97 Dim-to-Warm

SPECIFIC PRECAUTIONS - GENERAL GUIDELINES



Dimming not allowed



Lamp suitable for dimming only with specific dimmers
(A list of compatible dimmers shall be provided on the website www.megaman.cc)



Lamp not suitable for use if broken
(its outer case)

Lamp not suitable for use under dust and moisture

Indoor use only

Turn off the lamp and let it cool down before any replacement

Do not run LED and incandescent lights on a trailer

For lamps with a weight significantly higher than that of the lamps for which they are a replacement, attention should be drawn to the fact that the increased weight may reduce the mechanical stability of certain luminaires and lamp holders and may impair contact making and lamp retention.

TESTING CONDITIONS

Refer to Annex A of IEC 62612 method of measuring lamp characteristics
Light output and life hour are measured at 25°C, 230V

CALCULATIONS - GENERAL RULES

Refer to Annex II of Energy Labelling (EU) 2019/2015

Energy efficiency classes and calculation method

The energy efficiency class of light sources shall be determined as set out in Table 1, on the basis of the total mains efficacy η_{TM} , which is calculated by dividing the declared useful luminous flux Φ_{use} (expressed in lm) by the declared on-mode power consumption P_{on} (expressed in W) and multiplying by the applicable factor FTM of Table 2, as follows:

$$\eta_{TM} = (\Phi_{use}/P_{on}) \times FTM \text{ (lm/W)}$$

Table 1

Energy efficiency classes of light sources

Energy efficiency class	Total mains efficacy η_{TM} (lm/W)
A	$210 \leq \eta_{TM}$
B	$185 \leq \eta_{TM} < 210$
C	$160 \leq \eta_{TM} < 185$
D	$135 \leq \eta_{TM} < 160$
E	$110 \leq \eta_{TM} < 135$
F	$85 \leq \eta_{TM} < 110$
G	$\eta_{TM} < 85$

Table 2

Factors FTM by light source type

Light source type	Factor FTM
Non-directional (NDLS) operating on mains (MLS)	1,000
Non-directional (NDLS) not operating on mains (NMLS)	0,926
Directional (DLS) operating on mains (MLS)	1,176
Directional (DLS) not operating on mains (NMLS)	1,089

ADDITIONAL PART

A list of compatible dimmers shall be provided on the website www.megaman.cc

MEGAMAN GmbH
Halskestraße 22-26, AircomParc A1
40880 Ratingen
Germany

