

# MR16

## Reflector Lamps

ER045044-LNv00-WF+GU5.3+840+AD012

**MEGAMAN®**

35W/4.4W GU5.3 345lm 4000K Ra80 Non-Dim

### GENERAL DESCRIPTION

Model Number	ER045044-LNv00-WF
Product Code	ER045044-LNv00-WF+GU5.3+840+AD012
Model Identifier	711257/MM11257
Cap Base	GU5.3
Dimmable	No
Working Temperature	-30°C to +45°C

### TECHNICAL PARAMETERS

#### LIFE PERFORMANCE

Indicative Lifetime L70B50 (hrs)	15000	at 25°C
Number of Switching Cycles	> 100000	

#### ELECTRICAL DATA

On-mode Power (W)	4.4
Input Voltage	12 V
Frequency	N/A
Displacement Factor (cos φ1)	N/A
Equivalent Power (W)	35
Standby Power (W)	0.0
Networked Standby Power (W)	N/A
Survival Factor	0.90
Lumen Maintenance Factor	0.93

#### PHOTOMETRIC INFORMATION

Useful Luminous Flux (lm)	410
Useful Luminous Flux in 90° Cone (lm)	345
Useful Luminous Flux in 120° Cone (lm)	N/A
Correlated Colour Temperature (K)	4000
Colour Consistency	6
Colour Rendering Index	80
R9 Colour Rendering Index Value	0
Beam Angle (°)	36
Peak Luminous Intensity (cd)	700
Stroboscopic Effect Metric (SVM)	N/A
Flicker Metric (P <sub>st</sub> <sup>LM</sup> )	N/A
Chromaticity Coordinates (x and y)	0.382 0.380

#### ENERGY EFFICIENCY

Weighted Energy Consumption (kWh/1000hrs)	5
Energy Class	F

### CERTIFICATES & STANDARDS

Standards Compliance	IEC/EN 62838, IEC/EN 62493, IEC/EN 62471, ErP 2019/2020, IEC 62717, IEC CISPR15, EN 55015, IEC/EN 61547, IEC/EN 61000-3-2, IEC/EN 61000-3-3
Approvals	CE, RoHS

### DIMENSIONS & WEIGHT

Height (mm)	46
Width (mm)	50
Depth (mm)	50
Weight (g)	41

# MR16

## Reflector Lamps

ER045044-LNv00-WF+GU5.3+840+AD012



35W/4.4W GU5.3 345lm 4000K Ra80 Non-Dim

### SPECIFIC PRECAUTIONS - GENERAL GUIDELINES



Dimming not allowed



Lamp suitable for dimming only with specific dimmers  
(A list of compatible dimmers shall be provided on the website  
[www.megaman.cc](http://www.megaman.cc))



Lamp not suitable for use if broken  
(its outer case)



Lamp not suitable for use under dust and moisture

Indoor use only

Turn off the lamp and let it cool down before any replacement

Do not run LED and incandescent lights on a trailer

For lamps with a weight significantly higher than that of the lamps for which they are a replacement, attention should be drawn to the fact that the increased weight may reduce the mechanical stability of certain luminaires and lamp holders and may impair contact making and lamp retention.

### TESTING CONDITIONS

Refer to Annex A of IEC 62612 method of measuring lamp characteristics

Light output and life hour are measured at 25°C, 230V

# MR16

## Reflector Lamps

ER045044-LNv00-WF+GU5.3+840+AD012



35W/4.4W GU5.3 345lm 4000K Ra80 Non-Dim

### CALCULATIONS - GENERAL RULES

Refer to Annex II of Energy Labelling (EU) 2019/2015

#### Energy efficiency classes and calculation method

The energy efficiency class of light sources shall be determined as set out in Table 1, on the basis of the total mains efficacy  $\eta_{TM}$ , which is calculated by dividing the declared useful luminous flux  $\Phi_{use}$  (expressed in  $lm$ ) by the declared on-mode power consumption  $P_{on}$  (expressed in  $W$ ) and multiplying by the applicable factor FTM of Table 2, as follows:

$$\eta_{TM} = (\Phi_{use}/P_{on}) \times FTM \text{ (lm/W)}$$

Table 1

Energy efficiency classes of light sources

Energy efficiency class	Total mains efficacy $\eta_{TM}$ (lm/W)
A	$210 \leq \eta_{TM}$
B	$185 \leq \eta_{TM} < 210$
C	$160 \leq \eta_{TM} < 185$
D	$135 \leq \eta_{TM} < 160$
E	$110 \leq \eta_{TM} < 135$
F	$85 \leq \eta_{TM} < 110$
G	$\eta_{TM} < 85$

Table 2

Factors FTM by light source type

Light source type	Factor FTM
Non-directional (NDLS) operating on mains (MLS)	1,000
Non-directional (NDLS) not operating on mains (NMLS)	0,926
Directional (DLS) operating on mains (MLS)	1,176
Directional (DLS) not operating on mains (NMLS)	1,089

### ADDITIONAL PART

A list of compatible dimmers shall be provided on the website [www.megaman.cc](http://www.megaman.cc)

MEGAMAN GmbH  
Halskestraße 22-26, AircomParc A1  
40880 Ratingen  
Germany



© Copyright 2021. All rights reserved by MEGAMAN®

1/3/2022