PAR20,PAR30L,PAR38



Reflector Lamps

LR228110-HRv00-WF+E27+840+V0240

100W/11W E27 1050lm 4000K Ra80 Non-Dim

GENERAL DESCRIPTION	V
----------------------------	---

Model Number	LR228110-HRv00-WF
Product Code	LR228110-HRv00-WF+E27+840+V0240
Model Identifier	711725/MM11725
Cap Base	E27
Dimmable	No
Working Temperature	-30°C to +45°C

TECHNICAL PARAMETERS

LIFE PERFORMANCE

Indicative Lifetime L70B50 (hrs)	25000	at 25°C
Number of Switching Cycles	> 100000	

ELECTRICAL DATA

On-mode Power (W)	11	
Input Voltage	220-240 VAC	
Frequency	50/60 Hz	
Displacement Factor (cos φ1)	0.90	
Equivalent Power (W)	100	
Standby Power (W)	0.0	
Networked Standby Power (W)	N/A	
Survival Factor	0.90	
Lumen Maintenance Factor	0.96	

PHOTOMETRIC INFORMATION

Useful Luminous Flux (lm)	1300
Useful Luminous Flux in 90° Cone (Im)	1050
Useful Luminous Flux in 120° Cone (lm)	N/A
Correlated Colour Temperature (K)	4000
Colour Consistency	6
Colour Rendering Index	80
R9 Colour Rendering Index Value	0
Beam Angle (°)	36
Peak Luminous Intensity (cd)	2100
Stroboscopic Effect Metric (SVM)	0.4
Flicker Metric (P _{st} ^{LM})	1.0
Chromaticity Coordinates (x and y)	0.382 0.380

ENERGY EFFICIENCY

Weighted Energy Consumption (kWh/1000hrs)	11
Energy Class	E

CERTIFICATES & STANDARDS

Standards Compliance	IEC/EN 62560, IEC/EN 62493, IEC/EN 62471, ErP 2019/2020, IEC 62612, IEC CISPR15, EN 55015, IEC/EN 61547, IEC/EN 61000-3-2, IEC/EN 61000-3-3
Approvals	CE, RoHS

DIMENSIONS & WEIGHT

Height (mm)	105
Width (mm)	95
Depth (mm)	95
Weight (g)	92

PAR20,PAR30L,PAR38



LR228110-HRv00-WF+E27+840+V0240



100W/11W E27 1050lm 4000K Ra80 Non-Dim

SPECIFIC PRECAUTIONS - GENERAL GUIDELINES



Dimming not allowed

(its outer case)





Lamp suitable for dimming only with specific dimmers (A list of compatible dimmers shall be provided on the website www.megaman.cc)



Lamp not suitable for use under dust and moisture

Indoor use only

Lamp not suitable for use if broken

Turn off the lamp and let it cool down before any replacement

Do not run LED and incandescent lights on a trailer

For lamps with a weight significantly higher than that of the lamps for which they are a replacement, attention should be drawn to the fact that the increased weight may reduce the mechanical stability of certain luminaires and lamp holders and may impair contact making and lamp retention.

TESTING CONDITIONS

Refer to Annex A of IEC 62612 method of measuring lamp characteristics Light output and life hour are measured at 25°C, 230V

PAR20,PAR30L,PAR38



LR228110-HRv00-WF+E27+840+V0240



100W/11W E27 1050lm 4000K Ra80 Non-Dim

CALCULATIONS - GENERAL RULES

Refer to Annex II of Energy Labelling (EU) 2019/2015

Energy efficiency classes and calculation method

The energy efficiency class of light sources shall be determined as set out in Table 1, on the basis of the total mains efficacy η_{TM} , which is calculated by dividing the declared useful luminous flux Φ_{use} (expressed in lm) by the declared on-mode power consumption P_{on} (expressed in W) and multiplying by the applicable factor FTM of Table 2, as follows:

 $\eta TM = (\Phi use/Pon) \times FTM (Im/W)$

Table 1
Energy efficiency classes of light sources

Energy eniciency classes of right sources		
Energy efficiency class	Total mains efficacy ηTM (lm/W)	
Α	210 ≤ ηTM	
В	185 ≤ ηTM < 210	
С	160 ≤ ηTM < 185	
D	135 ≤ ηTM < 160	
E	110 ≤ ηTM < 135	
F	85 ≤ ηTM < 110	
G	ηTM < 85	

Table 2 Factors FTM by light source type

Light source type	Factor FTM
Non-directional (NDLS) operating on mains (MLS)	1,000
Non-directional (NDLS) not operating on mains (NMLS)	0,926
Directional (DLS) operating on mains (MLS)	1,176
Directional (DLS) not operating on mains (NMLS)	1,089

ADDITIONAL PART

A list of compatible dimmers shall be provided on the website www.megaman.cc

MEGAMAN GmbH Halskestraße 22-26, AircomParc A1 40880 Ratingen Germany



© Copyright 2021. All rights reserved by MEGAMAN®

3/10/2022